

1 Lists

To construct a list, one can use the `list` constructor, so `l = list()` returns an empty list. The constructor also takes any *iterable* object in Python and constructs a list from it. For example `list(range(5))` returns a new list equal to `[0, 1, 2, 3, 4]` and `list("cow")` returns a new list equal to `['c', 'o', 'w']`. One can use the square bracket notation to create lists too, so `[3, 1, 4, 1, 5, 9]` returns an appropriate list of length 6.

Operations

Lists, like strings, are sequences of objects, so they support the sequence operations:

- indexing,
- slicing, and
- length.

These operations are *not side-effecting*—they keep However, there are many differences between lists and strings:

- Lists are *mutable*, which means that we can change the contents of the list several of its methods. If `l` is a list, then the following operations are all popular methods for manipulating `l`:

index assignment `l[i] = obj` means replace the object at index `i` of `l` with `obj`.

appending `l.append(obj)` means append `obj` to `l` so that the length of `l` increases by one.

inserting `l.insert(i, obj)` means insert `obj` at index `i` of `l`; the length of the list increases by one.

popping `l.pop(i)` means delete the the object at index `i`; `l.pop()` means delete the last object.

deleting `del l[i]` means delete the object at index `i` of `l`; this decreases the length of the list by one.

removing `l.remove(obj)` means remove the first item in `l` that equals `obj`.

- Sort lists using the `sort()` method.
- Lists are *heterogenous*, which means they can simultaneously store objects of different type.
- Lists are really *adjustable arrays*, which we will examine in detail later.
- Lists support *list comprehensions*, which allow you to make new lists from other iterables. For example, to generate the first five non-negative multiples of 5, one could write:

```
[5*i for i in range(10)]
```

Let `l = list(range(10))`. What does `l` equal after the following operations?

```
l.append(11)
del l[0]
l.remove(1)
```

Let `l = list('sub pop')`. What does `l` equal after the following operations?

```
l.insert(3, '*')
l[len(l)-2] = 'u'
l.append('!')
l.append(l.pop())
```

2 Searching

A fundamental operation in computer science is *search*. Suppose we have a list of strings

```
l = ["The Strokes", "Bon Iver", "Arcade Fire", "The Black Keys",  
    "Pixies", "The White Stripes", "Neutral Milk Hotel",  
    "The National", "Yo La Tengo"]
```

and we want to be able to find a string in the list that begins with a certain prefix. Call this function `find_startswith(lst, s)` and consider its natural definition below:

```
1 def find_startswith(lst, searchstr):  
2     for s in lst:  
3         if s.startswith(searchstr):  
4             return s  
5     return None
```

Question 1. *In the worst case, if `lst` has n elements, how many elements will `find_startswith` examine?*

```
1 def find_startswith(lst, searchstr):  
2     low = 0  
3     high = len(lst) - 1  
4     while low < high:  
5         mid = (high + low) // 2  
6         if lst[mid].startswith(searchstr):  
7             return lst[mid]  
8         elif lst[mid] < searchstr:  
9             low = mid + 1  
10        else:  
11            high = mid - 1  
12    return None
```

Question 2. *In the worst case, if `lst` has n elements, how many elements will `find_startswith` examine?*